

**SLA RANGE - Constant Current Discharge Data**

<b>Amperes to 1.60 VPC ( at 20°C )</b>																	
<b>Time (min)</b>	<b>1</b>	<b>5</b>	<b>10</b>	<b>15</b>	<b>20</b>	<b>30</b>	<b>45</b>	<b>60</b>	<b>90</b>	<b>120</b>	<b>180</b>	<b>240</b>	<b>300</b>	<b>420</b>	<b>480</b>	<b>600</b>	<b>1200</b>
12 SLA 26	131	88.5	61.6	46.6	38.1	28.2	20.7	16.3	11.5	9.04	6.46	5.13	4.28	3.31	2.98	2.47	1.33
12 SLA 30	161	109	75.8	57.3	46.9	34.8	25.6	20.2	14.3	11.2	8.01	6.36	5.31	4.10	3.69	3.07	1.65
12 SLA 50	268	181	126	95.5	78.2	58.0	42.6	33.7	23.8	18.7	13.3	10.6	8.85	6.84	6.15	5.11	2.75
12 SLA 80	397	300	210	157	127	94.8	70.8	57.5	42.5	33.9	24.4	19.3	16.1	12.1	10.7	8.79	4.52
6 SLA 100	536	363	253	191	156	116	85.3	67.3	47.7	37.4	26.7	21.2	17.7	13.7	12.3	10.2	5.50
6 SLA 125	390	326	270	215	180	138	103	83.3	59.6	46.7	33.4	26.5	22.1	17.1	15.4	12.8	6.88
4 SLA 150	760	524	369	287	235	174	128	101	71.5	56.2	40.6	32.2	26.9	20.8	18.7	15.5	8.36
6 SLA 160	573	491	368	280	232	178	136	109	81.0	64.1	45.7	36.0	30.0	23.0	20.6	17.2	9.08
6 SLA 180	562	469	389	309	260	198	149	120	85.8	67.2	48.0	38.1	31.9	24.6	22.2	18.4	9.90
6 SLA 200	792	590	435	347	288	220	165	133	95.8	75.6	54.4	43.1	35.8	27.2	24.6	20.5	10.9
4 SLA 200	605	529	446	372	310	230	170	138	101	80.2	57.1	45.0	37.5	28.7	25.7	21.4	11.3
2 SLA 250	1004	750	567	451	375	286	213	168	119	93.3	67.6	54.4	45.6	34.6	31.0	25.6	14.0
2 SLA 300	1044	825	652	526	440	336	254	201	143	112	81.2	65.3	54.8	41.6	37.2	30.7	16.8
2 SLA 330	1541	1164	816	611	493	368	275	223	165	132	94.9	74.9	62.3	46.8	41.6	34.1	17.5
2 SLA 405/4	1641	1213	897	721	604	455	337	271	199	159	114	90.7	75.2	56.5	50.3	41.2	21.3
2 SLA 500	1652	1354	1076	863	719	543	406	325	237	187	133	106	88.5	68.4	61.5	51.1	27.5
2 SLA 580	1781	1493	1220	996	837	636	478	382	275	217	155	123	103	79.3	71.4	59.3	31.9
2 SLA 800	1698	1607	1432	1303	1127	882	664	534	398	321	235	187	156	117	105	86.2	46.5
2 SLA 1000	2123	2009	1790	1629	1409	1102	830	668	497	402	294	234	195	147	131	108	58.1
2 SLA 1500	2318	2065	1836	1635	1463	1231	977	818	705	524	394	315	266	208	187	155	86.7
2 SLA 2000	3091	2753	2449	2181	1950	1641	1303	1091	940	698	525	420	354	277	249	206	116

<b>Amperes to 1.65 VPC ( at 20°C )</b>																	
<b>Time (min)</b>	<b>1</b>	<b>5</b>	<b>10</b>	<b>15</b>	<b>20</b>	<b>30</b>	<b>45</b>	<b>60</b>	<b>90</b>	<b>120</b>	<b>180</b>	<b>240</b>	<b>300</b>	<b>420</b>	<b>480</b>	<b>600</b>	<b>1200</b>
12 SLA 26	114	84.6	59.0	45.3	37.1	27.7	20.3	16.0	11.4	8.98	6.44	5.12	4.27	3.30	2.97	2.47	1.33
12 SLA 30	140	104	72.6	55.7	45.7	34.2	25.1	19.8	14.1	11.1	7.98	6.34	5.30	4.09	3.69	3.06	1.65
12 SLA 50	234	173	121	92.8	76.2	57.0	41.9	33.0	23.5	18.5	13.3	10.6	8.83	6.82	6.14	5.10	2.74
12 SLA 80	369	264	201	152	123	92.5	69.5	56.6	41.9	33.5	24.2	19.1	15.9	12.0	10.6	8.74	4.49
6 SLA 100	468	347	242	186	152	114	83.7	65.9	46.9	37.1	26.6	21.1	17.7	13.6	12.3	10.2	5.48
6 SLA 125	350	307	255	206	176	134	101	81.7	58.7	46.3	33.3	26.4	22.1	17.1	15.4	12.8	6.86
4 SLA 150	638	498	357	278	228	171	126	99.4	70.9	56.0	40.4	32.1	26.9	20.7	18.7	15.5	8.34
6 SLA 160	560	481	352	271	226	174	133	107	79.9	63.0	45.2	35.6	29.6	22.6	20.3	17.0	8.99
6 SLA 180	505	442	368	297	253	193	145	118	84.5	66.7	47.9	38.0	31.8	24.6	22.1	18.4	9.87
6 SLA 200	754	568	423	339	283	217	163	131	95.0	75.0	53.8	42.9	35.6	27.1	24.5	20.4	10.9
4 SLA 200	574	508	430	361	304	225	166	135	99.8	78.8	56.5	44.5	37.0	28.3	25.4	21.2	11.2
2 SLA 250	872	692	533	429	364	279	209	165	117	92.4	67.0	54.0	45.4	34.5	30.9	25.5	14.0
2 SLA 300	905	754	610	498	423	328	249	198	141	111	80.4	64.8	54.4	41.4	37.0	30.6	16.8
2 SLA 330	1434	1025	780	591	479	359	270	220	163	130	93.9	74.3	61.8	46.5	41.3	33.9	17.4
2 SLA 405/4	1509	1154	869	721	591	447	333	267	197	157	114	90.0	74.8	56.0	49.9	41.0	21.2
2 SLA 500	1513	1271	1022	831	695	529	398	321	235	185	133	106	88.3	68.2	61.4	51.0	27.4
2 SLA 580	1681	1425	1166	962	811	618	468	378	272	215	154	123	102	79.1	71.2	59.2	31.8
2 SLA 800	1496	1423	1334	1215	1054	852	651	528	393	318	233	186	155	117	104	85.6	46.3
2 SLA 1000	1870	1779	1667	1519	1318	1065	814	660	492	397	291	233	194	146	130	107	57.9
2 SLA 1500	2117	1934	1748	1573	1406	1193	961	809	625	518	391	314	264	206	185	154	86.4
2 SLA 2000	2822	2579	2330	2097	1874	1590	1282	1078	834	690	521	418	352	275	247	205	115

<b>Amperes to 1.67 VPC ( at 20°C )</b>																	
<b>Time (min)</b>	<b>1</b>	<b>5</b>	<b>10</b>	<b>15</b>	<b>20</b>	<b>30</b>	<b>45</b>	<b>60</b>	<b>90</b>	<b>120</b>	<b>180</b>	<b>240</b>	<b>300</b>	<b>420</b>	<b>480</b>	<b>600</b>	<b>1200</b>
12 SLA 26	110	82.1	57.4	44.2	36.4	27.2	20.0	15.8	11.3	8.94	6.42	5.10	4.27	3.30	2.97	2.46	1.32
12 SLA 30	135	101	70.5	54.3	44.8	33.6	24.8	19.6	14.0	11.1	7.96	6.33	5.29	4.09	3.68	3.06	1.64
12 SLA 50	225	168	118	90.5	74.6	55.9	41.3	32.7	23.3	18.4	13.3	10.5	8.82	6.81	6.13	5.09	2.74
12 SLA 80	355	260	196	149	121	91.2	68.8	56.1	41.5	33.3	24.0	19.0	15.8	11.9	10.6	8.71	4.48
6 SLA 100	449	336	235	181	149	112	82.6	65.4	46.5	36.9	26.5	21.1	17.6	13.6	12.3	10.2	5.47
6 SLA 125	338	297	244	199	171	131	99.6	80.7	58.2	46.1	33.2	26.4	22.0	17.0	15.3	12.7	6.84
4 SLA 150	611	480	347	271	224	168	124	98.6	70.3	55.8	40.3	32.1	26.8	20.7	18.6	15.5	8.32
6 SLA 160	549	472	343	265	222	171	131	106	79.2	62.5	44.9	35.3	29.3	22.4	20.1	16.8	8.94
6 SLA 180	487	427	352	287	247	188	143	116	83.8	66.3	47.8	38.0	31.7	24.5	22.1	18.3	9.85
6 SLA 200	734	556	417	335	280	215	162	130	94.7	74.6	53.6	42.7	35.5	27.1	24.4	20.4	10.9
4 SLA 200	556	495	418	352	296	221	164	134	99.0	78.2	56.1	44.1	36.6	28.0	25.1	21.0	11.2
2 SLA 250	826	659	513	417	357	275	206	163	116	91.7	66.7	53.8	45.1	34.4	30.8	25.4	13.9
2 SLA 300	859	716	585	483	415	323	246	196	140	111	80.0	64.5	54.2	41.3	36.9	30.5	16.7
2 SLA 330	1377	1008	759	578	471	354	267	218	161	129	93.3	73.9	61.5	46.3	41.1	33.8	17.4
2 SLA 405/4	1456	1119	851	700	584	443	329	264	195	156	113	89.5	74.4	55.7	49.7	41.0	21.2
2 SLA 500	1462	1227	980	808	681	520	392	317	233	184	133	105	88.2	68.1	61.3	50.9	27.4
2 SLA 580	1601	1364	1119	928	787	605	462	373	270	214	154	122	102	79.0	71.1	59.1	31.7
2 SLA 800	1387	1329	1255	1164	1018	830	639	520	390	315	231	185	155	116	103	85.3	46.1
2 SLA 1000	1734	1662	1569	1455	1273	1038	798	650	488	393	289	232	193	145	129	107	57.6
2 SLA 1500	1976	1830	1661	1508	1367	1167	947	800	620	514	388	312	263	205	185	153	85.9
2 SLA 2000	2634	2440	2215	2010	1822	1556	1262	1067	827	686	517	416	351	274	246	204	115

Amperes to 1.70 VPC ( at 20°C )																	
Time (min)	1	5	10	15	20	30	45	60	90	120	180	240	300	420	480	600	1200
12 SLA 26	106	79.9	55.9	43.2	35.7	26.8	19.8	15.7	11.2	8.90	6.41	5.10	4.26	3.29	2.96	2.46	1.32
12 SLA 30	130	98.2	68.7	53.2	44.0	33.0	24.5	19.5	13.9	11.0	7.94	6.32	5.28	4.08	3.67	3.05	1.64
12 SLA 50	217	164	115	88.6	73.3	55.0	40.8	32.5	23.1	18.3	13.2	10.5	8.81	6.80	6.12	5.09	2.73
12 SLA 80	342	256	191	146	119	90.1	68.1	55.6	41.2	33.0	23.9	18.9	15.8	11.9	10.6	8.68	4.47
6 SLA 100	433	327	229	177	147	110	81.6	64.9	46.2	36.7	26.5	21.1	17.6	13.6	12.2	10.2	5.46
6 SLA 125	327	288	235	194	168	128	98.3	80.0	57.8	45.8	33.1	26.3	22.0	17.0	15.3	12.7	6.83
4 SLA 150	589	464	337	266	220	165	123	97.9	69.8	55.6	40.3	32.0	26.8	20.7	18.6	15.5	8.30
6 SLA 160	540	464	336	260	219	169	129	105	78.6	62.2	44.6	35.0	29.1	22.2	19.9	16.7	8.90
6 SLA 180	471	414	338	279	241	184	142	115	83.2	66.0	47.7	37.9	31.7	24.5	22.0	18.3	9.83
6 SLA 200	716	546	411	332	278	214	161	130	94.4	74.3	53.4	42.6	35.4	27.0	24.3	20.3	10.9
4 SLA 200	542	483	408	344	289	218	162	132	98.3	77.7	55.7	43.8	36.4	27.8	24.9	20.9	11.1
2 SLA 250	787	631	497	407	352	272	203	162	116	91.2	66.4	53.6	45.0	34.3	30.7	25.4	13.9
2 SLA 300	819	684	565	471	408	318	243	194	139	110	79.7	64.3	54.0	41.2	36.9	30.5	16.7
2 SLA 330	1328	994	742	568	463	350	264	216	160	128	92.8	73.5	61.2	46.1	41.0	33.7	17.4
2 SLA 405/4	1411	1088	836	682	577	439	326	262	193	155	112	89.1	74.1	55.5	49.5	40.9	21.2
2 SLA 500	1420	1189	944	788	669	513	388	315	231	183	132	105	88.1	68.0	61.2	50.9	27.3
2 SLA 580	1533	1313	1078	900	767	595	457	369	268	213	154	122	102	78.9	71.0	59.0	31.7
2 SLA 800	1294	1249	1189	1120	987	812	628	513	388	312	229	184	154	116	103	85.0	45.9
2 SLA 1000	1618	1561	1486	1400	1234	1015	785	642	484	390	287	231	193	145	129	106	57.4
2 SLA 1500	1856	1742	1587	1452	1334	1145	934	793	616	512	386	311	263	204	184	153	85.5
2 SLA 2000	2474	2322	2117	1936	1778	1526	1246	1058	822	682	514	414	351	273	246	203	114

Amperes to 1.75 VPC ( at 20°C )																	
Time (min)	1	5	10	15	20	30	45	60	90	120	180	240	300	420	480	600	1200
12 SLA 26	95.0	73.3	52.6	41.3	34.3	25.8	19.3	15.3	11.0	8.76	6.36	5.06	4.24	3.27	2.95	2.44	1.31
12 SLA 30	117	90.0	64.7	50.8	42.2	31.8	23.9	19.0	13.6	10.9	7.88	6.28	5.26	4.06	3.66	3.03	1.63
12 SLA 50	196	150	108	84.7	70.3	53.1	39.8	31.7	22.7	18.0	13.1	10.5	8.76	6.77	6.09	5.05	2.71
12 SLA 80	301	236	176	137	113	86.7	66.1	54.3	40.3	32.5	23.5	18.7	15.5	11.7	10.4	8.59	4.44
6 SLA 100	392	300	216	169	141	106	79.6	63.3	45.5	36.0	26.3	20.9	17.5	13.5	12.2	10.1	5.42
6 SLA 125	292	252	210	180	157	123	95.0	78.0	56.9	45.2	32.8	26.2	21.9	16.9	15.2	12.6	6.78
4 SLA 150	530	426	317	254	211	159	120	95.4	68.7	54.8	39.9	31.8	26.6	20.6	18.5	15.3	8.24
6 SLA 160	480	432	317	247	209	164	126	103	76.6	61.0	43.7	34.4	28.6	21.8	19.6	16.4	8.78
6 SLA 180	421	362	302	260	226	176	137	112	81.9	65.1	47.3	37.7	31.5	24.4	21.9	18.2	9.76
6 SLA 200	641	501	387	316	268	208	159	128	93.4	73.8	53.1	42.3	35.2	26.9	24.2	20.2	10.8
4 SLA 200	498	452	382	321	270	208	157	127	96.2	76.3	54.7	43.0	35.7	27.2	24.5	20.5	11.0
2 SLA 250	684	569	460	381	332	258	195	156	114	90.2	65.8	53.1	44.7	34.1	30.5	25.2	13.8
2 SLA 300	737	623	513	441	387	306	233	187	136	109	79.0	63.8	53.6	40.9	36.6	30.3	16.6
2 SLA 330	1167	915	682	533	440	336	257	211	157	126	91.1	72.4	60.3	45.5	40.5	33.4	17.2
2 SLA 405/4	1276	1010	792	653	555	425	319	256	188	151	110	87.1	72.5	54.4	48.7	40.7	21.0
2 SLA 500	1293	1058	856	731	631	491	376	308	227	181	131	105	87.6	67.7	60.9	50.5	27.1
2 SLA 580	1355	1173	970	837	723	568	443	362	264	210	152	121	102	78.5	70.7	58.6	31.5
2 SLA 800	1108	1089	1058	1006	910	770	603	499	377	307	227	182	152	114	102	84.2	45.5
2 SLA 1000	1385	1362	1323	1258	1137	963	754	623	472	383	283	228	191	143	128	105	56.9
2 SLA 1500	1589	1519	1430	1334	1236	1080	901	767	600	500	378	306	260	202	183	151	84.8
2 SLA 2000	2118	2025	1907	1778	1649	1440	1202	1023	800	666	504	408	346	270	244	202	113

Amperes to 1.80 VPC ( at 20°C )																	
Time (min)	1	5	10	15	20	30	45	60	90	120	180	240	300	420	480	600	1200
12 SLA 26	85.0	66.2	48.8	38.9	32.4	24.8	18.8	14.9	10.8	8.58	6.29	5.02	4.21	3.25	2.93	2.42	1.30
12 SLA 30	104	81.3	60.0	47.9	39.9	30.8	23.2	18.5	13.4	10.6	7.80	6.23	5.22	4.03	3.63	3.00	1.61
12 SLA 50	174	136	100.0	79.8	66.4	51.3	38.7	30.9	22.3	17.5	13.0	10.4	8.70	6.72	6.05	5.00	2.69
12 SLA 80	258	185	148	122	103	80.9	62.9	52.2	38.9	31.4	22.8	18.1	15.1	11.4	10.2	8.43	4.37
6 SLA 100	348	271	200	160	133	103	77.4	61.7	44.6	35.1	26.0	20.8	17.4	13.4	12.1	10.0	5.37
6 SLA 125	260	219	186	163	142	115	90.7	75.6	55.8	44.3	32.5	25.9	21.8	16.8	15.1	12.5	6.72
4 SLA 150	475	386	294	240	200	154	116	93.1	67.4	53.7	39.5	31.5	26.4	20.4	18.4	15.0	8.15
6 SLA 160	455	380	288	233	199	158	122	99.0	73.9	59.5	42.6	33.5	27.8	21.2	19.0	16.0	8.62
6 SLA 180	374	316	268	234	204	165	131	109	80.3	63.8	46.8	37.4	31.3	24.2	21.8	18.0	9.67
6 SLA 200	470	403	337	287	250	196	150	123	92.4	72.8	52.5	41.7	34.8	26.7	23.9	20.0	10.8
4 SLA 200	441	408	358	300	253	198	152	124	93.0	74.4	53.3	41.9	34.8	26.5	23.8	20.0	10.8
2 SLA 250	550	472	396	340	300	241	181	148	110	88.2	65.0	52.5	44.2	33.8	30.2	25.0	13.7
2 SLA 300	643	556	463	401	356	284	218	177	132	106	78.0	63.0	53.0	40.5	36.3	30.0	16.4
2 SLA 330	1000	720	576	474	401	314	244	203	151	122	88.4	70.4	58.7	44.4	39.5	32.7	17.0
2 SLA 405/4	1005	835	696	588	512	401	305	249	184	147	105	83.9	69.8	52.8	47.0	40.5	20.1
2 SLA 500	1088	903	769	664	582	462	361	298	221	177	130	104	87.0	67.2	60.5	50.0	26.9
2 SLA 580	1194	1007	864	753	662	540	421	347	257	206	151	120	101	78.0	70.2	58.0	31.2
2 SLA 800	979	968	937	900	829	707	565	471	362	296	221	178	149	112	100	82.0	44.5
2 SLA 1000	1223	1210	1172	1125	1037	884	707	588	452	370	277	222	186	140	125	103	55.6
2 SLA 1500	1383	1321	1245	1171	1094	980	833	722	575	485	368	300	254	199	180	150	82.8
2 SLA 2000	1845	1761	1660	1561	1458	1306	1111	962	767	646	490	400	338	266	240	200	110

Amperes to 1.85 VPC ( at 20°C )																	
Time (min)	1	5	10	15	20	30	45	60	90	120	180	240	300	420	480	600	1200
12 SLA 26	67.8	53.2	41.1	33.4	28.6	21.8	16.5	13.3	10.1	8.11	5.95	4.79	4.04	3.12	2.81	2.35	1.26
12 SLA 30	77.0	62.4	48.5	39.4	33.8	26.2	20.0	16.5	12.5	10.1	7.38	5.94	5.00	3.87	3.48	2.91	1.56
12 SLA 50	121	102	82.2	68.7	57.8	45.0	34.0	27.5	20.8	16.8	12.3	9.90	8.34	6.45	5.81	4.85	2.60
12 SLA 80	150	130	109	94.6	83.9	69.4	56.9	47.2	35.4	28.5	20.9	16.6	13.9	10.7	9.57	7.89	4.12
6 SLA 100	242	205	164	137	116	90.0	67.9	55.0	41.6	33.5	24.6	19.8	16.7	12.9	11.6	9.70	5.20
6 SLA 125	218	188	159	139	125	104	84.1	70.4	52.0	41.9	30.8	24.8	20.9	16.1	14.5	12.1	6.51
4 SLA 150	333	281	228	195	169	132	99.6	82.5	62.5	50.3	36.9	29.7	25.0	19.4	17.4	14.6	7.81
6 SLA 160	325	279	235	199	175	139	110	90.4	70.1	57.1	41.4	32.6	27.0	20.4	18.2	15.3	8.21
6 SLA 180	314	270	230	201	180	150	121	101	74.9	60.3	44.3	35.6	30.0	23.2	20.9	17.5	9.37
6 SLA 200	370	330	280	243	217	175	138	116	87.4	70.6	51.1	40.7	34.0	26.1	23.5	19.5	10.4
4 SLA 200	371	346	302	252	209	169	130	110	83.3	67.0	49.2	39.6	33.4	25.8	23.2	19.4	10.4
2 SLA 250	459	398	340	295	262	211	162	138	104	83.8	61.5	49.5	41.7	32.3	29.0	24.3	13.0
2 SLA 300	551	478	407	353	314	254	195	165	125	101	75.8	61.3	51.5	39.2	35.2	29.1	15.8
2 SLA 330	581	503	423	367	326	269	221	183	138	111	81.3	64.6	54.1	41.4	37.2	30.6	16.0
2 SLA 405/4	767	665	560	484	424	343	277	228	169	136	96.7	77.4	64.5	48.9	43.8	38.5	19.1
2 SLA 500	881	767	662	572	511	424	335	276	208	168	123	99.0	83.4	64.5	58.1	48.5	26.0
2 SLA 580	975	866	740	654	587	489	392	327	241	194	143	115	96.7	74.8	67.3	56.3	30.2
2 SLA 800	829	823	809	763	704	604	489	409	325	272	206	169	141	106	94.9	78.3	41.3
2 SLA 1000	1036	1029	1011	953	880	754	612	512	407	340	257	211	176	133	119	97.9	51.7
2 SLA 1500	1137	1095	1043	984	932	855	741	653	531	445	346	285	240	188	169	142	77.2
2 SLA 2000	1517	1460	1390	1313	1243	1140	988	870	708	594	462	380	320	250	226	190	103

Amperes to 1.90 VPC ( at 20°C )																	
Time (min)	1	5	10	15	20	30	45	60	90	120	180	240	300	420	480	600	1200
12 SLA 26	29.9	27.9	25.1	22.6	20.9	17.4	14.0	11.5	9.01	7.26	5.29	4.23	3.54	2.69	2.43	2.04	1.10
12 SLA 30	44.9	40.3	34.9	29.6	25.9	21.6	17.3	14.3	11.2	9.00	6.55	5.24	4.39	3.34	3.01	2.53	1.36
12 SLA 50	61.9	57.7	52.0	46.8	43.1	36.0	28.9	23.8	18.6	15.0	10.9	8.74	7.31	5.57	5.02	4.21	2.27
12 SLA 80	107	95.8	85.4	75.8	69.6	58.2	47.5	40.5	31.6	25.5	18.7	14.9	12.4	9.46	8.53	7.11	3.78
6 SLA 100	124	115	104	93.5	86.2	72.0	57.8	47.6	37.2	30.0	21.8	17.5	14.6	11.1	10.0	8.42	4.53
6 SLA 125	155	144	130	117	108	90.1	72.2	59.5	46.5	37.5	27.3	21.9	18.3	13.9	12.6	10.5	5.67
4 SLA 150	186	173	156	140	129	108	86.6	71.4	55.8	45.0	32.8	26.2	21.9	16.7	15.1	12.6	6.80
6 SLA 160	198	185	166	150	137	112	90.7	76.6	61.5	49.7	36.2	29.1	24.5	18.6	16.5	13.6	7.25
6 SLA 180	223	208	187	168	155	130	104	85.7	67.0	54.0	39.3	31.5	26.3	20.0	18.1	15.2	8.16
6 SLA 200	256	239	215	194	178	149	124	106	80.2	65.5	47.6	38.1	31.9	24.6	22.1	18.8	10.1
4 SLA 200	252	242	217	199	172	144	116	95.2	74.4	60.0	43.7	35.0	29.2	22.3	20.1	16.8	9.07
2 SLA 250	309	289	260	234	215	180	144	119	93.0	75.0	54.6	43.7	36.6	27.8	25.1	21.1	11.3
2 SLA 300	371	346	312	281	259	216	173	143	112	90.0	65.5	52.4	43.9	33.4	30.1	25.3	13.6
2 SLA 330	416	372	332	294	270	226	185	157	123	99.0	72.6	57.7	48.3	36.7	33.1	27.6	14.7
2 SLA 405/4	568	507	443	393	353	301	244	204	152	122	88.5	70.8	59.2	45.1	40.7	35.1	18.2
2 SLA 500	586	541	494	448	415	349	286	238	186	150	109	87.4	73.1	55.7	50.2	42.1	22.7
2 SLA 580	717	670	603	542	500	418	335	276	216	174	127	101	84.8	64.6	58.2	48.8	26.3
2 SLA 800	696	686	672	640	586	509	430	368	295	248	183	149	125	92.7	84.5	71.0	37.3
2 SLA 1000	869	857	840	800	733	636	537	460	369	310	229	186	156	116	106	88.7	46.7
2 SLA 1500	935	899	859	816	762	692	605	542	454	391	307	257	219	170	154	129	69.8
2 SLA 2000	1246	1198	1146	1087	1016	922	807	722	605	521	410	342	292	227	205	172	93.0